



D201

IP VIDEO DOOR STATION

Full Stainless-Steel · Surface-Mounted



TECHNICAL SPECIFICATIONS



GENER	AL		
Housing		Front panel 3 mm (0,12 in) brushed Stainless steel, galvanized steel sheet surface- mounted housing	
Doorbell	button	Stainless-steel button with illuminated LED Ring	
Namepla		Illuminated	
Mountin		Surface-mounted	
Power su	ıpply	15 V DC (power 110 - 240 V AC) or Power over Ethernet (PoE 802.3af Mode-A)	
Weight		1.25 kg	
Connecto	ors	Power, electric door opener/strike, door chime, door opener button, network	
Weathe	r protection	Yes, IP65	
Approva	ls	CE, IC, FCC, IP65	
Dimensio	ons	215 x 125 x 55 mm (H x W x D) 8,46 x 4,92 x 2,17 in (H x W x D)	
Operatin	g conditions	-20 to +40°C / -4 to 104°F Humidity 10 to 85 % RH (non condensing)	
Scope c	of delivery	Video Door Station, front panel, surface- mounted housing, power supply unit (world- wide, 110 - 240 V), DIN-Rail power supply sold separately, screw package, Quickstart Guide, 2 x 1 m (39,37 in) antenna extension cable, 2 x external antenna	
EAN		4260423860124	
Warranty	1	see www.doorbird.com/warranty	
CURRE	CURRENT SYSTEM REQUIREMENTS		
Mobile d	evice	Latest iOS on iPhone/iPad, latest Android on Smartphone/Tablet	
Internet		High-Speed landline broadband internet connection, DSL, cabel or fiber, min. 500 kbs uploadbandwith, no socks- or proxyserver	
Network		802.11 b/g/n 2.4 GHz or Ethernet network, with DHCP	
Recomm installati	nended on height	Camera lens should be at a min. height of 145 cm (57 in). Before the installation please determine your optimal installation height.	

VIDEO	
Camera	HDTV 720 p, dynamic (VGA - HDTV)
Lens	High-end ultra wide-angle hemispheric lens 180° horizontal, 90° vertical, straightened, IR-capable
Night-vision	Yes, light sensor, automatic IR-cut filter, 12 IR-LEDs
AUDIO	
Audio components	Speaker and microphone, echo and noise cancellation
Audio streaming	Two-way duplex
NETWORK	
WiFi	802.11 b/g/n 2.4 GHz
Ethernet	Connector, PoE
MOTION SENSOR	
Туре	Passive infrared sensor (PIR)
Detection angle	180°
Range	2 - 8 m (79 - 315 in) depends on environment
INTEGRATED WIRE	ELESS MODULES
WiFi	2,4 GHz, external antenna
OPTIONAL ACCESS	SORIES
Sold separately	see www.doorbird.com/buy

Special remarks:

The assembly requires professional skills or technician.

TECHNICAL DRAWINGS

DoorBird Technology meets Design.

Front panel, data in mm Material thickness: 3,0







