









GENERAL	
Housing	Front panel 3 mm (0,12 in) brushed Stainless steel with bronze finish by electroplating, galvanized steel sheet flush-mounted housing
Doorbell button	Stainless-steel button with illuminated LED Ring
Nameplate	Illuminated
Mounting type	Flush-mounted
Power supply	15 V DC (power 110 - 240 V AC) or Power over Ethernet (PoE 802.3af Mode-A)
Weight	1,25 kg
Connectors	Power, electric door opener/strike, door chime, door opener button, network
Weather protection	Yes, IP65
Approvals	CE, IC, FCC, IP65
Dimensions	215 x 125 x 59 mm (H x W x D) 8,46 x 4,92 x 2,32 in (H x W x D)
Operating conditions	-20 to +40°C / -4 to 104°F Humidity 10 to 85 % RH (non condensing)
Scope of delivery	Video Door Station, front panel, flush- mounted housing, power supply unit (world-wide, 110 - 240 V), DIN-Rail power supply sold separately, screw package, quick start guide, 2 x 1m (39,37 in) antenna extension cable, 2 x external antenna
EAN	4260423860186
Warranty	see www.doorbird.com/warranty

VIDEO	
Camera	HDTV 720 p, dynamic (VGA - HDTV)
Lens	High-end ultra wide-angle hemispheric lens 180° horizontal, 90° vertical, straightened, IR-capable
Night-vision	Yes, light sensor, automatic IR-cut filter, 12 IR-LEDs

AUDIO

Audio components	Speaker and microphone, echo and noise cancellation
Audio streaming	Two-way duplex

NETWORK	
WiFi	802.11 b/g/n 2.4 GHz
Ethernet	Connector, PoE

MOTION SENSOR

Туре	Passive infrared sensor (PIR)
Detection angle	180°
Range	2 - 8 m (79 - 315 in) depends on environment

INTEGRATED WIRELESS MODULES

WiFi

2,4 GHz, external antenna

OPTIONAL ACCESSORIES

Sold separately

see www.doorbird.com/buy

Special remarks: The assembly requires professional skills or technician.

802.11 b/g/n 2.4 GHz or Ethernet

CURRENT SYSTEM REQUIREMENTS

or proxyserver

network, with DHCP

installation height.

Latest iOS on iPhone/iPad, latest

Android on Smartphone/Tablet

High-Speed landline broadband internet connection, DSL, cabel or fiber,

min. 500 kbs uploadbandwith, no socks-

Camera lens should be at a min. height

of 145 cm (57 in). Before the installation

please determine your optimal

Recommended installation height

Mobile device

Internet

TECHNICAL DRAWINGS



Front panel, data in mm Material thickness: 3,0



















