





TECHNICAL SPECIFICATIONS	D1101V SURFACE-MOUNT & FLUSH-MOUNT	D101 & D101S
Camera	Sony 1080p image sensor	720p image sensor
Material	Flush-mount: Full stainless steel Surface-mount: Stainless steel front panel	Polycarbonate
Relays	1 Bistable switching relay Normal state and switching behavior configurable	1 Monostable relay Normal state not configurable: normally open
Motion sensor	4D Motion sensor with configurable direction and range	PIR Infrared motion sensor with configurable zones
Audio	Extended AEC, ANR (echo and noise cancellation) higher volume possible	Extended AEC, ANR (echo and noise cancellation)
Mounting type	Surface-mounted Flush-mounted Angle mounting adapter for tricky installation spots (separately available)	Surface-mounted
Connection method	Screw connection terminal plug for hassle-free installation	Conventional adapter cables for installation
Simultaneous video streams	One, for event-based recording to NVR/NAS devices	One, for continuous or event-based recording to NVR/NAS devices
WDR (wide dynamic range)	Digital WDR for clear image in sunlit and dark conditions	
Access control	Via smartphone, tablet and IP indoor stations Via Bluetooth BLE (released with future firmware update)	Via smartphone, tablet and IP indoor stations